


Declaration Of Performance
DOP.04430008

Essential characteristics	Leistung Performance	+DUPROH/NON6WDGDUW +DUPRO/HGWHFKQDO VSHFLILFDWLRQ
Tolerances on dimensions and shape	EN ISO 13920: 1996-11	EN 1090- 1:2009+A1:2011
Elongation	EN 10025-2: 2004	
Tensile strength	EN 10025-2: 2004	
Yield strength		
Impact strength	NPD	
Weldability (chemical composition)	EN 10025-2: 2004	
Suitability for HDG	EN 10025-2: 2004	
Reaction to fire	EWDE EWHHO	EN 13501-1
Noise Protection	NPD	-
Enerji tasarrufu Energy efficiency	NPD	-
Durability	hUOHUDDONLNRURRURRURVDKLSWLU ;11,62HWHVNGDOGOPDDOYDQVED EN ISO 12944'e göre kaplanabilir. Products have the following corrosion protection: HDG acc. DIN EN ISO 1461, it can be additional coated acc. EN ISO 12944	EN 1090-2
Product marking	Her parti UDDDUMLDUHWOHPHVLYHWLS EHOLUOHPHVLLHWDQDOELOLU Any product batch can be identified applied charge marking and type designation.	-

X NDUÖDNLUOHULSHUIRUPDÖVDEORGDOLVWHOHEHDEIGLOHSHUIRUPDÖNDUÖNHOLU
KHSHUIRUPDEHRIWKHHQLVWHGSGURGKWLFRD'IPWRWKHGHFODUHGSHUIRUPDEHLVDEOH

/DÖPDDO
6LH GIRUDGREHKDOIRI/,1.E\

N

ietimi
OL

gF

Kalite Yönetimi
40