

CERTIFICATE OF COMPLIANCE

Certificate Number EX27136
Report Reference EX27136-20170620
Issue Date 2020-JULY-27

Issued to: LINK YAPI SANAYI VE TICARET A S
Gebze Organize Sanayi Bolgesi
1000 Sokak No 1016
Cayirova / KOCAELI TURKEY

**This certificate confirms that
representative samples of**

SWAY-BRACE DEVICES, RIGID TYPE FOR SPRINKLER
SYSTEMS

See Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: ANSI/UL 203A Standard for Safety for Sway Brace Devices
for Sprinkler System Piping

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up
Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's
Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number EX27136
Report Reference EX27136-20170620
Issue Date 2020-JULY-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Sway-Brace Devices, Rigid Type for Sprinkler Systems

Structure Attachment Fitting:

Model	Bracing Member Type	Bracing Member Size, in	Bracing Direction	Load Rating, lbf (kgf)	Comments
RSBA	Schedule 40	1, 1-1/4	N/A	1370 (620)	-
RSBE	Schedule 40	1, 1-1/4	N/A	1370 (620)	-
RSBI	N/A	N/A	Par, Perp, Vert	1370 (620)	I-beam attachment fitting for use with flange sizes 3/8 to 0.7 in. For use only with the model RSBE.

Par = Horizontal flange w/ parallel load
Perp = Horizontal flange w/ perpendicular load
Vert = Vertical flange



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

